



FORM PTO-1390 (Modified) (REV 11-2000)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER <b>SHC0169</b>
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371			U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR <b>10/088662</b>
INTERNATIONAL APPLICATION NO. <b>PCT/JP00/06480</b>	INTERNATIONAL FILING DATE <b>21 September 2000</b>	PRIORITY DATE CLAIMED <b>21 September 1999</b>	
TITLE OF INVENTION <b>DISPOSABLE ABSORBENT WEARING ARTICLE AND PROCESS FOR PLACEMENT OF ELASTIC MEMBERS ASSOCIATED WITH LEG HOLES ON THE ARTICLE</b>			
APPLICANT(S) FOR DO/EO/US <b>Naoto Ohashi et al.</b>			
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:			
<ol style="list-style-type: none"> <li>1. <input checked="" type="checkbox"/> This is a <b>FIRST</b> submission of items concerning a filing under 35 U.S.C. 371.</li> <li>2. <input type="checkbox"/> This is a <b>SECOND</b> or <b>SUBSEQUENT</b> submission of items concerning a filing under 35 U.S.C. 371.</li> <li>3. <input type="checkbox"/> This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (24) indicated below.</li> <li>4. <input checked="" type="checkbox"/> The US has been elected by the expiration of 19 months from the priority date (Article 31).</li> <li>5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371 (c) (2)) <ol style="list-style-type: none"> <li>a. <input type="checkbox"/> is attached hereto (required only if not communicated by the International Bureau).</li> <li>b. <input checked="" type="checkbox"/> has been communicated by the International Bureau.</li> <li>c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US).</li> </ol> </li> <li>6. <input checked="" type="checkbox"/> An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)). <ol style="list-style-type: none"> <li>a. <input checked="" type="checkbox"/> is attached hereto.</li> <li>b. <input type="checkbox"/> has been previously submitted under 35 U.S.C. 154(d)(4).</li> </ol> </li> <li>7. <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3)) <ol style="list-style-type: none"> <li>a. <input type="checkbox"/> are attached hereto (required only if not communicated by the International Bureau).</li> <li>b. <input type="checkbox"/> have been communicated by the International Bureau.</li> <li>c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired.</li> <li>d. <input checked="" type="checkbox"/> have not been made and will not be made.</li> </ol> </li> <li>8. <input type="checkbox"/> An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).</li> <li>9. <input type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).</li> <li>10. <input type="checkbox"/> An English language translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).</li> <li>11. <input checked="" type="checkbox"/> A copy of the International Preliminary Examination Report (PCT/IPEA/409).</li> <li>12. <input type="checkbox"/> A copy of the International Search Report (PCT/ISA/210).</li> </ol>			
<b>Items 13 to 20 below concern document(s) or information included:</b>			
<ol style="list-style-type: none"> <li>13. <input type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98.</li> <li>14. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.</li> <li>15. <input checked="" type="checkbox"/> A <b>FIRST</b> preliminary amendment.</li> <li>16. <input type="checkbox"/> A <b>SECOND</b> or <b>SUBSEQUENT</b> preliminary amendment.</li> <li>17. <input type="checkbox"/> A substitute specification.</li> <li>18. <input type="checkbox"/> A change of power of attorney and/or address letter.</li> <li>19. <input type="checkbox"/> A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.</li> <li>20. <input checked="" type="checkbox"/> A second copy of the published international application under 35 U.S.C. 154(d)(4).</li> <li>21. <input type="checkbox"/> A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).</li> <li>22. <input checked="" type="checkbox"/> Certificate of Mailing by Express Mail</li> <li>23. <input checked="" type="checkbox"/> Other items or information: <ul style="list-style-type: none"> <li>- -English translation of Examination Report and letters of July 16, 2001 in Japanese and the substitute pages for amendments</li> <li>- -Application Data Sheet</li> </ul> </li> </ol>			

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 1.101) <b>10/088662</b>		INTERNATIONAL APPLICATION NO. <b>PCT/JP00/06480</b>		ATTORNEY'S DOCKET NUMBER <b>SHC0169</b>	
24. The following fees are submitted: <b>BASIC NATIONAL FEE ( 37 CFR 1.492 (a) (1) - (5)) :</b> <input type="checkbox"/> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO ..... <b>\$1040.00</b> <input checked="" type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO ..... <b>\$890.00</b> <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO ..... <b>\$740.00</b> <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) ..... <b>\$710.00</b> <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) ..... <b>\$100.00</b> <div style="text-align: right;"><b>ENTER APPROPRIATE BASIC FEE AMOUNT =</b></div>				<b>CALCULATIONS PTO USE ONLY</b>  <div style="border: 1px solid black; height: 100px; width: 100%;"></div>	
Surcharge of <b>\$130.00</b> for furnishing the oath or declaration later than _____ months from the earliest claimed priority date (37 CFR 1.492 (e)): <input type="checkbox"/> 20 <input type="checkbox"/> 30				<b>\$0.00</b>	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	8 - 20 =	0	x \$18.00	<b>\$0.00</b>	
Independent claims	2 - 3 =	0	x \$84.00	<b>\$0.00</b>	
Multiple Dependent Claims (check if applicable). <input type="checkbox"/>				<b>\$0.00</b>	
<b>TOTAL OF ABOVE CALCULATIONS =</b>				<b>\$890.00</b>	
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.				<b>\$0.00</b>	
<b>SUBTOTAL =</b>				<b>\$890.00</b>	
Processing fee of <b>\$130.00</b> for furnishing the English translation later than _____ months from the earliest claimed priority date (37 CFR 1.492 (f)). <input type="checkbox"/> 20 <input type="checkbox"/> 30				<b>\$0.00</b>	
<b>TOTAL NATIONAL FEE =</b>				<b>\$890.00</b>	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable). <input type="checkbox"/>				<b>\$0.00</b>	
<b>TOTAL FEES ENCLOSED =</b>				<b>\$890.00</b>	
				Amount to be refunded	\$
				charged	\$
a. <input checked="" type="checkbox"/> A check in the amount of <b>\$890.00</b> to cover the above fees is enclosed. b. <input type="checkbox"/> Please charge my Deposit Account No. _____ in the amount of _____ to cover the above fees. A duplicate copy of this sheet is enclosed. c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. <b>02-0385</b> A duplicate copy of this sheet is enclosed. d. <input type="checkbox"/> Fees are to be charged to a credit card. <b>WARNING:</b> Information on this form may become public. <b>Credit card information should not be included on this form.</b> Provide credit card information and authorization on PTO-2038.					
<b>NOTE:</b> Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.					
SEND ALL CORRESPONDENCE TO:					
Michael S. Gzybowski Baker & Daniels 111 East Wayne Street, Suite 800 Fort Wayne, IN 46802 (260) 424-8000			<div style="text-align: center;">             SIGNATURE         </div> <div style="text-align: center;"> <b>Michael S. Gzybowski</b>            NAME         </div> <div style="text-align: center;"> <b>32,816</b>            REGISTRATION NUMBER         </div> <div style="text-align: center;"> <b>March 20, 2002</b>            DATE         </div>		

PATENT APPLICATION*IN THE UNITED STATES PATENT AND TRADEMARK OFFICE*

<i>Group</i>		}	<u>Certificate Under 37 C.F.R. 1.10</u>
<i>Art Unit:</i>	Unknown	}	"EXPRESS MAIL" MAILING LABEL NUMBER
		}	EL905872485US
<i>Attorney</i>		}	DATE OF DEPOSIT <u>March 20, 2002</u>
<i>Docket No.:</i>	SHC0169	}	I HEREBY CERTIFY THAT THIS PAPER OR FEE IS BEING
		}	DEPOSITED WITH THE UNITED STATES POSTAL SER-
<i>Applicant:</i>	Naoto Ohashi et al.	}	VICE "EXPRESS MAIL POST OFFICE TO ADDRESSEE"
		}	SERVICE UNDER 37 C.F.R. 1.10 ON THE DATE
<i>Invention:</i>	DISPOSABLE ABSORBENT WEARING	}	INDICATED ABOVE AND IS ADDRESSED TO THE ASSIS-
	ARTICLE AND PROCESS FOR	}	TANT COMMISSIONER FOR PATENTS WASHINGTON, DC
	PLACEMENT OF ELASTIC MEMBERS	}	20231.
	ASSOCIATED WITH LEG HOLES ON	}	
	THE ARTICLE	}	on <u>March 20, 2002</u>
		}	
		}	Michelle L. Neal
<i>Serial No:</i>	Unknown	}	
<i>Filed:</i>	Herewith	}	
<i>Internat'l Serial</i>	PCT/JP00/06480	}	
<i>Internat'l Filing</i>		}	
<i>Date:</i>	September 21, 2000	}	
<i>Earliest Priority</i>		}	
<i>Date:</i>	September 21, 1999	}	
<i>Examiner:</i>	Unknown	}	

PRELIMINARY AMENDMENT

Box PCT  
 Attn: DO/EO/US  
 Assistant Commissioner for Patents  
 Washington, DC 20231

Sir:

Prior to the examination of the above-identified application, please amend the application  
 as follows:

IN THE TITLE

Please change the title to read "DISPOSABLE ABSORBENT WEARING ARTICLE  
 AND PROCESS FOR PLACEMENT OF ELASTIC MEMBERS ASSOCIATED WITH LEG  
 HOLES ON THE ARTICLE"

IN THE SPECIFICATION

Please replace the last paragraph beginning on page 4 and continuing on the top of page 5 with the following:

- -The disposable absorbent wearing article further comprising the plurality of elastic members associated with leg-holes are converged substantially into respective single bundles along first elastic zones each extending over a given length of the crotch region in the longitudinal direction of the article and are spaced one from another along second and third elastic zones extending from the first elastic zone along respective side edges of the front and rear waist regions over a given length and the elastic members associated with the leg-holes present a tensile stress not higher in the first elastic zone than in the second and third elastic zones and said first, second and third elastic zones of said elastic members associated with the leg-holes are contiguous one to another.- -

IN THE CLAIMS

Please amend Claim 1 as follows:

1. (Amended) A disposable absorbent wearing article having a longitudinal direction and a transverse direction orthogonal to said longitudinal direction, comprising an absorbent structure including a liquid-pervious topsheet, a liquid-impervious backsheet, a liquid-absorbent core disposed therebetween and a pair of side flaps extending outward from transversely opposite side edges of said core, a plurality of elastic members associated with leg-holes being placed on cutouts formed in said side flaps to surround the thighs of a wearer,

said disposable absorbent wearing article further comprising:

said plurality of elastic members associated with leg-holes being converged substantially into respective single bundles along first elastic zones each extending over a given length of said crotch region in said longitudinal direction of said article and being spaced one from another

along second and third elastic zones extending from said first elastic zone along respective side edges of said front and rear waist regions over a given length; and

said elastic members associated with the leg-holes having a tensile stress not higher in said first elastic zone than in said second and third elastic zones and said first, second and third elastic zones of said elastic members associated with the leg-holes are contiguous one to another.

**•••REMARKS•••**


By the present Preliminary Amendment, the specification and claim have been revised to incorporate changes made to the international application prior to national phase entry and to more clearly describe applicants' invention in accordance with the requirements of 35 U.S.C. § 112.

Care has been taken so as to avoid the addition of new matter in the specification and claims.

Entry of the present Preliminary Amendment prior to the examination of the application is respectfully requested.

In the event applicants have overlooked the need for an extension of time, an additional extension of time, payment of fee, or additional payment of fee, applicants hereby petition therefor and authorize that any charges be made to Deposit Account No. 02-0385, Baker & Daniels.

Respectfully submitted,

  
Michael S. Gzybowski  
Reg. No. 32,816

BAKER & DANIELS  
111 East Wayne Street  
Suite 800  
Fort Wayne, Indiana 46802  
(260) 460-1661

MSG/mln/226706

## VERSION WITH MARKINGS TO SHOW CHANGES MADE

Changes Made to Specification Paragraphs

The last paragraph beginning on page 4 and continuing on the top of page 5 has been amended as follows:

The disposable absorbent wearing article further [comprise] comprising the plurality of elastic members associated with leg-holes are converged substantially into respective single bundles along first elastic zones each extending over a given length of the crotch region in the longitudinal direction of the article and are spaced one from another along second and third elastic zones extending from the first elastic zone along respective side edges of the front and rear waist regions over a given length and the elastic members associated with the leg-holes present a tensile stress not higher in the first elastic zone than in the second and third elastic zones and said first, second and third elastic zones of said elastic members associated with the leg-holes are contiguous one to another.

Changes Made to Claims

Claim 1 has been amended as follows:

1. A disposable absorbent wearing article having a longitudinal direction and a transverse direction orthogonal to said longitudinal direction, comprising an absorbent structure including a liquid-pervious topsheet, a liquid-impervious backsheet, a liquid-absorbent core disposed therebetween and a pair of side flaps extending outward from transversely opposite side edges of said core, a plurality of elastic members associated with leg-holes being placed on cutouts formed in said side flaps to surround the thighs of a wearer,

said disposable absorbent wearing article further comprising:

said plurality of elastic members associated with leg-holes being converged substantially

into respective single bundles along first elastic zones each extending over a given length of said crotch region in said longitudinal direction of said article and being spaced one from another along second and third elastic zones extending from said first elastic zone along respective side edges of said front and rear waist regions over a given length; and

said elastic members associated with the leg-holes having a tensile stress not higher in said first elastic zone than in said second and third elastic zones and said first, second and third elastic zones of said elastic members associated with the leg-holes are contiguous one to another.



2002年 3月19日 18時12分

白浜国際特許事務所

NO. 2088 P. 5

u/pv

11-267691/2000-272169

-1-

# S P E C I F I C A T I O N

DISPOSABLE ABSORBENT WEARING ARTICLE AND PROCESS FOR PLACEMENT  
OF ELASTIC MEMBERS ASSOCIATED WITH LEG-HOLES ON THE ARTICLE

## TECHNICAL FIELD

This invention relates to disposable absorbent wearing articles such as a diaper, a pad for incontinent or a sanitary napkin and a process for placement of elastic members associated with leg-holes on such articles.

## BACKGROUND ART

The invention relating to such articles, particularly to such article provided along respective thigh-surrounding zones with a plurality of rubber threads as elastic members associated with leg-holes and the invention relating to a process for placement of these rubber threads are disposed in Japanese Patent Application Nos. 1992-122257A and 1992-317650A. The process for making the disposable diaper is generally classified into a process according to which the thigh-surrounding zones of individual finished products extend in the machine direction (so-called lengthwise or end-to-end arranged process) and a process according to which the thigh-surrounding

2002年 3月19日 18時12分

台浜国際特許事務所

NO. 2088 P. 6

11-267691/2000-272169

-2-

zones of individual finished products extend in the direction orthogonal to the machine direction (so-called laterally running or side-by-side arranged process). The inventions disclosed in the above-cited Applications are classified into the former process. Generally, the former process is suitable for making a so-called open-type diaper having its front and rear waist regions connected to each other immediately before actual use to meet requirements for mass-production of the diaper at desired high velocity. The latter process, on the other hand, is suitable for making a so-called pants-type or pull-on-type diaper having its front and rear waist regions previously connected to each other. The invention relating to the latter process in which a plurality of elastic members are preferably placed along each of the thigh-surrounding zones is disclosed in Japanese Patent Application No. 1991-33201A.

The above-cited Japanese Patent Application Nos. 1992-122257A and 1992-317650A disclose the process for placement of continuous elastic members associated with the leg-holes. According to this process, a continuous web as a component material for the diaper is provided along its transversely opposite side edges with adhesive zones arranged intermittently in the longitudinal direction, then elastic members associated with the respective leg-holes, each

2002年 3月19日 18時12分

白浪国際特許事務所

NO. 2088 P. 7

11-267691/2000-272169

-3-

comprising a plurality of elastic elements, are fed under tension onto the respective adhesive zones and secured thereto so that the elastic members associated with the leg-holes may describe generally sinusoidal curves. According to this process of prior art, these elastic members associated with the leg-holes are forcibly traversed against tensile force of these elastic members so as to extend across the continuous web. Consequently, the elastic members associated with the leg-holes present a tensile stress higher in a generally middle zone than the remaining zone in a crotch region of the diaper.

Placement of the elastic members associated with the leg-holes in this manner causes these elastic members to present a tensile stress higher in the middle zone than in the remaining zone, resulting in that gathers formed in the middle zone of the crotch region do not easily extend as the diaper is worn. Gaps between the wearer's skin and the gathers may cause leak of body fluids. Additionally, it is likely that the diaper as a whole might shift from its proper position and a liquid-absorbent core might be twisted and deformed as the crotch region of the diaper shifts due to a movement of the wearer's thighs. These factors also may cause leak of body fluids and, in addition, might create a feeling of discomfort against the wearer. In case of a diaper provided on its side flaps on which

11-267691/2000-272169

- 4 -

the elastic members associated with the leg-holes are placed and these side flaps are provided, in turn, with elastic barrier flaps, there is an additional anxiety that relatively high tensile stress of the elastic members associated with the leg-holes might prevent the barrier flaps from rising as sufficiently high as expected.

It is an object of this invention to solve such problems as have been described above in disposable absorbent wearing articles such as a disposable diaper.

#### DISCLOSURE OF THE INVENTION

According to this invention, there is provided a disposable absorbent wearing article having a longitudinal direction and a transverse direction orthogonal to the longitudinal direction, the article comprising an absorbent structure including a liquid-pervious topsheet, a liquid-impervious backsheet, a liquid-absorbent core disposed therebetween and a pair of side flaps extending outward from transversely opposite side edges of the core, a plurality of elastic members associated with leg-holes being placed on cutouts formed in the side flaps to surround the thighs of a wearer.

The disposable absorbent wearing article further

11-267691/2000-272169

- 5 -

comprise the plurality of elastic members associated with leg-holes are converged substantially into respective single bundles along first elastic zones each extending over a given length of the crotch region in the longitudinal direction of the article and are spaced one from another along second and third elastic zones extending from the first elastic zone along respective side edges of the front and rear waist regions over a given length and the elastic members associated with the leg-holes present a tensile stress not higher in the first elastic zone than in the second and third elastic zones.

According to another aspect of this invention, there is provided a process for placement of elastic members associated with leg-holes on a disposable absorbent wearing article, comprising the steps of:

(a) feeding a continuous web as a component of the article in its longitudinal direction at a given velocity and at the same time continuously coating the continuous web along its transversely opposite side edges extending its longitudinal direction with a hot melt adhesive to form first and second adhesive zones;

(b) feeding first and second continuous elastic members associated with the leg-holes, each comprising a plurality of continuous elastic members spaced one from another and under

11-267691/2000-272169

-6-

tension, onto the first and second adhesive zones, respectively, in such a manner that the first and second elastic members associated with the leg-holes may extend across the first and second adhesive zones of the continuous web beyond respective inner and outer side edges of the first and second adhesive zones and respectively describe generally sinusoidal curves about the respective adhesive zones with respective first zones of the first and second elastic members associated with the leg-holes lying on the first and second adhesive zones being fixed to the first and second adhesive zones, respectively, and respective second zones of the first and second elastic members associated with the leg-holes extending beyond inner side edges of the first and second adhesive zones being contractibly shifted to the first and second adhesive zones so as to be fixed to the first and second adhesive zones, respectively; and

(c) cutting the continuous web along lines extending in its transverse direction across respective third zones of the first and second continuous elastic members associated with the leg-holes together with the first and second continuous elastic members associated with the leg-holes so that thereupon the third zones may contract.

The invention includes the following embodiments:

The core has a stiffness of 1 - 30gf·cm (10 - 300mN·cm)

11-267691/2000-272169

- 7 -

in the longitudinal and transverse directions.

The elastic members associated with the leg-holes are respectively spaced in the first elastic zones from the side edges of the core at least by 10mm. According to still another preferred embodiment of this invention relating to the article, the elastic members associated with the leg-holes in the second and third elastic zones are progressively diverged as these elastic members extend in the front and rear waist regions.

The process further includes the steps of placing liquid-absorbent cores on given zones on the continuous web defined between the first and second adhesive zones at given intervals in the longitudinal direction of the web and placing and bonding second continuous web upon and to the first continuous web so as to cover the liquid-absorbent cores.

The first and second adhesive zones are formed by continuously coating the transversely opposite side edges of the first continuous web with hot melt adhesive so as to describe a plurality of spirals extending in the longitudinal direction of the first continuous web.

The first continuous web is made-of liquid-impervious material and the second continuous web is made of liquid-pervious material.

11-267691/2000-272169

- 8 -

## BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a partially cutaway perspective view showing a disposable diaper;

Fig. 2 is a plan view illustrating relative positions of a backsheet, a core and elastic members associated with leg-holes;

Fig. 3 is a diagram schematically illustrating a process for making the diaper; and

Fig. 4 is a partially-enlarged diagram illustrating steps III and IV in Fig. 3.

## PREFERRED EMBODIMENTS OF THE INVENTION

Embodiments of this invention will be described in more details with reference to the accompanying drawings.

(1) A diaper as one embodiment of a disposable absorbent wearing article according to this invention:

Referring to Fig. 1, a diaper 1 as a specific embodiment of a disposable absorbent wearing article has a longitudinal center line 2 and provided with an absorbent structure 1A. The diaper 1 has a longitudinal direction and a transverse direction orthogonal to this longitudinal direction. The absorbent structure 1A has its side halves symmetric about the longitudinal center line 2, and comprises a liquid-pervious



2002年 3月19日 18時14分

白河國際特許事務所

NO. 2088 P. 13

11-267691/2000-272169

- 9 -

topsheet 3, a liquid-impervious backsheet 4, a liquid-absorbent core 5 interposed between these sheets 3, 4, a pair of side flaps 6 and a pair of end flaps 7, both pairs being formed by portions of the top- and backsheets 3, 4 extending outward beyond a peripheral edge of the core 5. The diaper 1 is composed of a front waist region 8, a rear waist region 9 and a crotch region 10. Though not shown, the side flaps 6 and/or the end flaps 7 are highly flexible and may be formed also by a suitable material other than the material for the topsheet 3 and/or the backsheet 4. In the crotch region 10, the side flaps 6 are formed with cutouts 11 to define leg-holes. Along curved side edges of these cutouts 11, elastic members 12 having rubber elasticity and comprising a plurality of elastic string or strands are secured under extension between the top- and backsheets 3, 4 by means of a hot melt adhesive 70 as will be described later. In the front and rear waist regions 8, 9, the end flaps 7 are also provided with elastic members 13A, 13B having rubbery elasticity. These elastic members 13A, 13B are also secured under extension to the top- and backsheets 3, 4 by means of a hot melt adhesive (not shown). It should be understood that, in the diaper 1, the elastic members 13A, 13B may be eliminated in one of the front and rear waist regions 8, 9.

11-267691/2000-272169

- 10 -

The topsheet 3 is provided on its transversely opposite side edges with barrier flaps 15 normally biased by elastic members 14 under extension. When the diaper 1 is worn and bent toward front and rear directions contraction of the elastic members 14 functions to uprise the barrier flaps 15 on the upper surface of the topsheet 3 and prevents bodily discharges on the topsheet 3 from flowing outward of the diaper and leaking sideways. The barrier flaps 15 have proximal edges 15a and distal edges 15b wherein the proximal edges 15a are joined between the respective side edges of the core 5 and the elastic members 12 by means of well known joining means(not shown) such as a hot melt adhesive or heat-welding. While longitudinally opposite ends of the barrier flaps 15 are collapsed outward away from the center line 2 and bonded to the topsheet 3 in such a collapsed state in Fig. 1, it is also possible to collapse these ends toward the center line 2 and join them to the topsheet 3 as well.

The core 5 is so-called semi-rigid and interposed in a substantially fixed state between the top- and backsheets 3, 4. As a means for such fixation, the well known hot melt adhesive coating in an appropriate pattern (not shown) is preferably used. In the longitudinal direction as well as in the transverse direction of the diaper 1, the core 5 preferably

11-267691/2000-272169

- 11 -

has a stiffness of 1 - 30gf·cm (10 - 300mN·cm) as measured in accordance with JIS P-8125 so that the elastic members may present a desired tensile stress.

Fig. 2 is a plan view illustrating relative positions of the backsheet 4, the core 5 and the respective elastic members 12, 14 in the diaper 1.

A plurality of the elastic members 12 are converged substantially in a single bundle in a middle zone (first elastic zone) S of the crotch region 10 and progressively diverged from this middle zone S toward front and rear side edge zones (second and third elastic zones) F, B in order to assure that the tensile stress in the middle zone S is not higher than that in the front and rear side edge zones F, B. The description "...tensile stress in the middle zone S is not higher..." used herein means that the tensile stress in the middle zone S is substantially equal to or lower than that in the front and rear side edge zones F, B. Under this requirement, length of the middle zone S is at least 30mm, preferably 50 - 150mm; tensile stress in the middle zone S is at least 30g/25mm width (300mN/25mm width), preferably 50 - 200g/25mm width (500 - 2000mN); tensile stress in the front and rear side edges F, B is at least 50g/25mm width, preferably 80 - 230mm width (800 - 2300mN/25mm width). The values of the tensile stress are those obtained on test pieces

11-267691/2000-272169

- 12 -

with 25mm in width cut off from the side flap 6 mainly in the elastic members 12 and stretched by 88.9%. Distance D between the elastic members 12 and the side edge of the core 5 in the middle zone S is at least 10mm, preferably 15 - 50mm. The maximum dimension between each pair of the adjacent elastic members 12 in the front and rear side edge zones F, B is 3 - 15mm.

On the transversely opposite side edges of the rear waist region 9, the absorbent structure 1A is provided with tape fastener 17 as shown in Fig. 1 to connect the rear waist region 9 to the front waist region 8 so that the absorbent structure 1A can be used as the diaper 1.

While contraction of the elastic members 12 in the diaper 1 generates a plurality of gathers along the middle zones S as well as along the front and rear side edge zones F, B, the tensile stress of the elastic members 12 along the middle zones S is not so high that the number of the gathers and the depth of the gathers trough are equal to or less than those in the front and rear side edges zones F, B. With a consequence, the diaper 1 comes in close in contact with the wearer's skin in the wearer's crotch region without formation of any significant gap between the wearer's skin and the gathers. In this way, there is no anxiety that leak of bodily discharges might occur in the crotch

11-267691/2000-272169

- 13 -

region 10 of the diaper 1, in particular, beyond the middle zones S thereof.

The unique arrangement that the elastic members 12 are spaced from the respective side edges of the core 5 by the distance D along the middle zones S of the diaper 1 and have relatively low tensile stress advantageously restricts a possibility that contraction of the elastic members 12 in the zones S might affect the core 5 as well as the barrier flaps 15. For example, it is not apprehended that contraction of the elastic members 12 in the zones S might twist, deform or crease the core 5 or obstruct the barrier flaps 15 to uprise. Furthermore, there is no anxiety that the absorbent structure 1A might be displaced from its proper position by following stretch or contraction of the elastic members 12 due to a movement of the wearer's legs.

(2) A process for placement of the elastic members associated with leg-holes on the diaper as a specific embodiment of the disposable absorbent wearing article:

Fig. 3 is a process diagram schematically illustrating a process for making the diaper 1 provided with the absorbent structure 1A. In the step I, first web 504 made of a continuous liquid-imperious plastic film is supplied to the process at a given rate from the left as viewed in the diagram.

11-267691/2000-272169

- 14 -

In the step II, a plurality of streaks of a hot melt adhesive 70 are discharged from nozzles 69A, 69B onto transversely opposite side edges of the first web 504 drawing a spiral pattern and providing a first adhesive zone 71A and a second adhesive zone 71B.

In the step III, a plurality of first continuous elastic members 512A and a plurality of second continuous elastic members 512B are fed under extension, by first and second traverse means 70A, 70B reciprocating in a direction orthogonal to the direction in which the first web 504 is being fed, onto the first and second adhesive zones 71A, 71B of the first web 504 so that the respective elastic members may be kept spaced from one another. The first and second continuous elastic members 512A, 512B fed in this manner extend across the respective adhesive zones 71A, 71B beyond respective inner side edges 72A, 72B and respective outer side edges 73A, 73B of the first and second adhesive zones 71A, 71B so as to describe substantially sinusoidal curves along the respective adhesive zones 71A, 71B. Respective first zones 74A, 74B of the first and second continuous elastic members 512A, 512B associated with the leg-holes lying on the respective adhesive zones 71A, 71B are fixed to these adhesive zones 71A, 71B and respective second zones 76A, 76B of the first and second continuous elastic

11-267691/2000-272169

- 15 -

members 512A, 512B associated with the leg-holes extending outward beyond the respective inner side edges 72A, 72B of the adhesive zones 71A, 71B are contractibly shifted toward the respective adhesive zones 71A, 71B so that these second zones 76A, 76B may be fixed to the respective adhesive zones 71A, 71B. The second zones 76A, 76B are converged in single bundles, respectively.

In the step IV, absorbent cores 505 are disposed on the first web 504 in such zones as defined at given intervals in the longitudinal direction of the first web 504 and a plurality of elastic members 513 associated with the waist-hole extending in the transverse direction of the first web 504 are bonded in an elongated state to the first web 504 in the zones defined between each pair of the adjacent cores 505, 505.

In the step V, a second web 503 formed of continuous liquid-pervious sheet is placed upon and bonded to the first web 504 so as to cover the cores 505 and the elastic members 513 associated with the waist-hole to obtain a laminate 501A. Though not illustrated, the first web 504 and the second web 503 may be bonded to each other using a hot melt adhesive or welding technique.

In the step VI, elastically stretchable first and second continuous flap members 515A, 515B are bonded, while applying

11-267691/2000-272169

- 16 -

tension in the advancing direction of the second web 503 being fed, to the upper surface of the second web 503 along transversely opposite side edges of the laminate 501A. Each of the first and second continuous flap members 515A, 515B comprises a narrow web 81 having transversely opposite side edges 515a and 515b. The one side edge 515b is provided with elastic members 514 bonded under extension and the other side edge 515a is secured to the second web 503. Tape fasteners 517A, 517B are attached to the laminate 501A in given zones along its transversely opposite side edges.

In the step VII, the side edges of the laminate 501A are cut off in a semicircular shape along the first and second continuous elastic members 512A, 512B associated with the leg-holes. Then the laminate 501A is cut along lines 82 transversely extending between each pair of the adjacent cores 505, 505 so as to bisect a plurality of elastic members 513 associated with the waist-hole in two direction of the second web 503 being fed and thereby individual diapers 1 are obtained.

Fig. 4 is a scale-enlarged diagram schematically illustrating the steps III and IV of Fig. 3. Referring to Fig. 4, imaginary lines indicate a manner in which the first and second continuous elastic members 512A, 512B associated with the leg-holes are fed by the respective traverse means 70A, 70B



11-267691/2000-272169

- 17 -

and solid lines indicate state of these members 512A, 512B immediately after they have been fed.

The first and second continuous elastic members 512A, 512B are fed so that these members 512A, 512B extend across the first and second adhesive zones 71A, 71B, respectively, beyond both the inner side edges 72A, 72B and the outer side edges 73A, 73B. After having been fed in this manner, the zones 76A, 76B extending beyond the inner side edges 72A, 72B are contractibly shifted so as to extend rectilinearly along the inner side edges 72A, 72B, respectively. The third zones 77A, 77B extending beyond the outer side edges 73A, 73B also are contractibly shifted so as to extend rectilinearly along the outer side edges 73A, 73B, respectively. These third zones 77A, 77B are also cut when the laminate 501A is cut in the step VII. These third zones 77A, 77B may be either secured or not to the first and second continuous adhesive zones 71A, 71B, respectively. If these zones 77A, 77B are secured to the adhesive zones 71A, 71B, respectively, these zones are kept to extend rectilinearly along the outer side edges 73A, 73B even after having been cut and if these zones 77A, 77B are not bonded to the adhesive zones 71A, 71B, respectively, these zones 77A, 77B further contract as these zones are cut. Figs. 1 - 3 shows the diaper 1 in which the third zones 77A, 77B have further contracted.

11-267691/2000-272169

- 18 -

The main stock materials used in the process for making the article as has been described correspond to the respective members in the diaper 1 shown in Figs. 1 and 2 as follows: the first continuous web 504 and the second continuous web 503 correspond to the backsheet 4 and topsheet 3; the core 505 corresponds to the core 5; the first and second continuous elastic members 512A, 512B associated with the leg-holes correspond to the elastic members 12 associated with the leg-holes; the fixed zones 74A, 74B of the first and second elastic members 512A, 512B associated with the leg-holes correspond to the front and back side edge zones 12F, 12B; the zones 76A, 76B of the first and second elastic members 512A, 512B extending along the inner side edges 72A, 72B of the first and second continuous adhesive zones 71A, 71B correspond to the middle side edge zones 12S of the elastic members 12 associated with the leg-holes; the third zones 77A, 77B of the first and second continuous elastic members 512A, 512B associated with the leg-holes extending along the outer side edges 73A, 73B of the first and second continuous adhesive zones 71A, 71B without being bonded to these adhesive zones 71A, 71B contract and define ends of the front and back side edge zones 12F, 12B of the elastic members 12 associated with the leg-holes; and the elastic members 513 associated with the waist-hole

11-267691/2000-272169

- 19 -

corresponding to the front and rear elastic members 13A, 13B associated with the waist-hole.

For the absorbent structure 1A and the diaper 1 made in the manner as has been described above, it is possible to ensure that the second zones 76A, 76B of the first and second continuous elastic members 512A, 512B associated with the leg-holes extending beyond the inner side edges 72A, 72B of the first and second adhesive zones 71A, 71B have the tensile stress decreased with respect to the initial tensile stress thereof in the course of being fed, specifically, equal to or less than the tensile stress presented by the fixed first zones 74A, 74B of the elastic members 512A, 512B, depending on the extension with which the first and second continuous elastic members 512A, 512B are fed onto the first web 504. For example, these elastic members 512A, 512B may be fed so that a stretch ratio of these elastic members 512A, 512B gradually increases as these elastic members 512A, 512B get nearer to the center line bisecting the width of the first web 504 and then the second zones 76A, 76B extending beyond the inner side edges 72A, 72B of the first and second adhesive zones 71A, 71B contract in order to achieve such effect. The elastic members 512A, 512B are converged and considerably spaced from the curved side edges of the core 505 surrounding the thighs. The diaper 1 having such first and second

11-267691/2000-272169

- 20 -

continuous elastic members 512A, 512B associated with the leg-holes corresponds to the diaper shown by Fig. 1 as the typical embodiment.

While this invention has been described on the basis of the disposable diaper 1 as the one embodiment, this invention is applicable also to the other disposable absorbent wearing article such as pad for incontinent or sanitary napkin. The elastic members 12 associated with the leg-holes are attached to the side flaps 6 of such article and these side flaps 6 may be formed by the topsheet 3 and/or the backsheet 4 or may be formed by a separate sheet replacing at least one of these sheets 3, 4. Furthermore, the coating pattern of the hot melt adhesive 70 for attachment of the elastic members 12, 512A, 512B associated with the leg-holes is not limited to the spiral pattern as illustrated and the other pattern such as appropriate curves or straight lines may be used. In addition, the first web 504 and the second web 503 may be coated along the side edges thereof with the adhesive in the form of many small dots which define substantially continuous adhesive zones.

The elastic members associated with the leg-holes present the tensile stress not higher along the middle side edge zones than along the front and rear side edge zones in the crotch region. Accordingly, the number as well as the depth of the gathers

11-267691/2000-272169

- 21 -

formed along the middle side edge zones are equal to or less than those along the front and rear side edge zones. Along the middle side edge zones, the wearing article is held in close contact with the thighs without leaving any significant gap between the wearer's skin and the gathers which might cause leak of body fluids. In spite of the arrangement that the elastic members associated with the leg-holes extending along the middle side edge zones are considerably spaced from the side edges of the core, it is not likely that stretch and contraction of the elastic members associated with the leg-holes along the middle side edges might cause the core to be twisted and/or cause the article worn to slip down along the thighs.

The process according to this invention for placement of the elastic members associated with the leg-holes allows the disposable absorbent wearing article to be continuously made in the unique manner such that the elastic members associated with the leg-holes present the tensile stress not higher along the middle side edges than along the front and rear side edges of the wearing article's crotch region.

11-267691/2000-272169

- 22 -

## C L A I M S

1. A disposable absorbent wearing article having a longitudinal direction and a transverse direction orthogonal to said longitudinal direction, comprising an absorbent structure including a liquid-pervious topsheet, a liquid-impervious backsheet, a liquid-absorbent core disposed therebetween and a pair of side flaps extending outward from transversely opposite side edges of said core, a plurality of elastic members associated with leg-holes being placed on cutouts formed in said side flaps to surround the thighs of a wearer,

said disposable absorbent wearing article further comprising:

said plurality of elastic members associated with leg-holes being converged substantially into respective single bundles along first elastic zones each extending over a given length of said crotch region in said longitudinal direction of said article and being spaced one from another along second and third elastic zones extending from said first elastic zone along respective side edges of said front and rear waist regions over a given length; and

said elastic members associated with the leg-holes having

11-267691/2000-272169

- 23 -

a tensile stress not higher in said first elastic zone than in said second and third elastic zones.

2. The article according to Claim 1, wherein said core has a stiffness of 1 - 30gf·cm (10 - 300mN·cm) in said longitudinal and transverse directions.

3. The article according to Claim 1, wherein said elastic members associated with the leg-holes are respectively spaced in said first elastic zones from said side edges of said core at least by 10mm.

4. The article according to Claim 1, wherein said elastic members associated with the leg-holes in said second and third elastic zones are progressively diverged as these elastic members extend in said front and rear waist regions.

5. A process for placement of elastic members associated with leg-holes on disposable absorbent wearing article, comprising the steps of:

(a) feeding a continuous web as a component of said article in its longitudinal direction at a given rate and at the same time continuously coating said continuous web along its transversely

11-267691/2000-272169

- 24 -

opposite side edges extending its longitudinal direction with hot melt adhesive to form first and second adhesive zones;

(b) feeding first and second continuous elastic members associated with the leg-holes, each comprising a plurality of continuous elastic members spaced one from another and under extension, onto said first and second adhesive zones, respectively, in such a manner that said first and second elastic members associated with the leg-holes may extend across said first and second adhesive zones of said continuous web beyond respective inner and outer side edges of said first and second adhesive zones and respectively describe substantially sinusoidal curves about said respective adhesive zones with respective first zones of said first and second elastic members associated with the leg-holes lying on said first and second adhesive zones being fixed to said first and second adhesive zones, respectively, and respective second zones of said first and second elastic members associated with the leg-holes extending beyond said inner side edges of said first and second adhesive zones being contractibly shifted to said first and second adhesive zones so as to be fixed to said first and second adhesive zones, respectively; and

(c) cutting said continuous web along lines extending in its transverse direction across respective third zones of said



11-267691/2000-272169

- 25 -

first and second continuous elastic members associated with the leg-holes together with said first and second continuous elastic members associated with the leg-holes so that thereupon said third zones may contract.

6. The process according to Claim 5, further including the steps of placing liquid-absorbent cores on given zones on said continuous web defined between said first and second adhesive zones at given intervals in the longitudinal direction of said web and placing and bonding second continuous web upon and to said first continuous web so as to cover said liquid-absorbent cores.

7. The process according to Claim 5, wherein said first and second adhesive zones are formed by continuously coating said transversely opposite side edges of said first continuous web with hot melt adhesive so as to describe a plurality of spirals extending in the longitudinal direction of said first continuous web.

8. The process according to Claim 5, wherein said first continuous web is made of liquid-impervious material and said second continuous web is made of liquid-pervious material.


11-267691/2000-272169

- 26 -

## A B S T R A C T

A disposable body fluid absorbent wearing article such as a disposable diaper includes elastic members 12 associated with leg-holes each having a plurality of elastic members which are placed along cutouts of side flaps 6 to surround a wearer's thighs. The elastic members 12 associated with the leg-holes are converged into respective single bundles along first elastic zones S of a crotch region 10 and diverged in second and third elastic zones F, B extending forward and backward from the first elastic zones S so that the elastic members 12 associated with the leg-holes may have a tensile stress not higher along the first elastic zones S than in the second and third elastic zones F, B.


1/4



第1図


2/4

第2図




3/4

第3図



4 / 4



第4図

ATTORNEY'S DOCKET NO. SHC0169

PCT/USA NATIONAL DECLARATION AND POWER OF ATTORNEY  
FOR U.S. PATENT APPLICATIONS  
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE  
UNDER 35 U.S.C. SECTION 371(c) (4)

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name:

I verily believe I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural inventors are named below) of the invention described and

claimed in international application No. PCT/JP00/06480 entitled: DISPOSABLE ABSORBENT WEARING ARTICLE AND PROCESS FOR PLACEMENT OF ELASTIC MEMBERS ASSOCIATED WITH LEG HOLES ON THE ARTICLE

and as amended on \_\_\_\_\_ (if any), which I have reviewed, and I understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above and for which I solicit a patent; that I do not know and do not believe that this invention was ever known or used in the United States of America before my or our invention or discovery thereof, or patented or described in any printed publication in any country before my or our invention or discovery thereof, or more than one year prior to my international application; that this invention was not in public use or on sale in the United States of America for more than one year prior to my international application; that this invention has not been patented or made the subject of an inventor's certificate issued before the date of my international application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months before my international application; that I acknowledge my duty to disclose information of which I am aware which is material to patentability of this application; and that prior to filing said international application, applications for patent or inventor's certificate on this invention of discovery which have been filed by me or my legal representatives or assigns in any country foreign to the United States of America are as follows:

(a) none filed more than 12 months prior to said international application, unless named below:

(b) earliest filed less than 12 months prior to said international application (the priority of which is hereby claimed under 35 U.S.C. Section 365):

11-267691 filed September 21, 1999

2000-272169 filed September 7, 2000

I hereby claim the benefit under Title 35, United States Code, §120, of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information material to patentability as defined in Title 37, Code of Federal Regulations, §1.56, which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

(Application Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)
--------------------------	---------------	---

As a named inventor, I hereby appoint John F. Hoffman, Regis. No. 26,280; Anthony Niewyk, Regis. No. 24,871; Kevin R. Erdman, Regis. No. 33,687; Michael D. Smith, Regis. No. 40,181; Michael S. Gzybowski, Regis. No. 32,816; Michael D. Schwartz, Regis. No. 44,326; Scott M. Lohnes, Regis. No. 45,451; Steven M. Hanley, Regis. No. P-46,756; Adam F. Cox, Regis. No. P-46,644; Arthur R. Whale, Regis. No. 18,778; Edward J. Prein, Regis. No. 37,212; Michael D. Beck, Regis. No. 32,722; Deborah R. Beck, Regis. No. 37,370; Jeffrey A. Michael, Regis. No. 37,394; Eric J. Groen, Regis. No. 32,230; Gerard T. Gallagher, Regis. No. 39,679; and Robert D. Null, Regis. No. 40,746; of BAKER & DANIELS, as attorney(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

SEND CORRESPONDENCE TO:

Michael S. Gzybowski  
BAKER & DANIELS  
111 East Wayne Street, Suite 800  
Fort Wayne, IN 46802

DIRECT TELEPHONE CALLS TO:

Michael S. Gzybowski  
BAKER & DANIELS  
111 East Wayne Street, Suite 800  
Fort Wayne, IN 46802

I declare further that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

The undersigned hereby authorizes the U.S. attorney or agent named herein to accept and follow instructions from \_\_\_\_\_ as to any action to be taken in the Patent and Trademark Office regarding this application without direct communication between the U.S. attorney or agent and the undersigned. In the event of a change in the persons from who instructions may be taken, the U.S. attorney or agent named herein will be so notified by the undersigned.

Full name of sole or first inventor: Naoto Ohashi

170 Residence Kagawa, JAPAN JPK Citizenship Japan

Post Office Address c/o Technical Center, Uni-Charm Co., Ltd., 1531-7, Takasuka,  
Wadahama, Toyohama-cho, Mitoyo-gun, Kagawa 769-1602 JAPAN

Inventor's Signature 天橋直人 Date July, 9, 2002

Full name of second joint inventor: Nariaki Shimoe

20 Residence Kagawa, JAPAN JPK Citizenship Japan

Post Office Address c/o Technical Center, Uni-Charm Co., Ltd., 1531-7, Takasuka,  
Wadahama, Toyohama-cho, Mitoyo-gun, Kagawa 769-1602 JAPAN

Inventor's Signature Nariaki Shimoe Date July September 4, 2002  
N.S.

Full name of third joint inventor: \_\_\_\_\_

Residence \_\_\_\_\_ Citizenship \_\_\_\_\_

Post Office Address \_\_\_\_\_

Inventor's Signature \_\_\_\_\_ Date \_\_\_\_\_

Full name of fourth joint inventor: \_\_\_\_\_

Residence \_\_\_\_\_ Citizenship \_\_\_\_\_

Post Office Address \_\_\_\_\_

Inventor's Signature \_\_\_\_\_ Date \_\_\_\_\_